

BURNDY - INSTALLING DIES FOR MAC ALUMINUM CONNECTORS

Cable Size	Die Index	Y34A	Y35	Y39	Y46*	Y48B	Y486B	Y60B
6	7	A5CR	U5CRT	U5CRT	U5CRT	-	-	-
4	8	A4CR	U4CRT	U4CRT	U4CRT	-	-	-
2	10	A2CR	U2CRT	U2CRT	U2CRT	-	-	-
1	11	A1CR	U1CRT	U1CRT	U1CRT	-	-	-
1/0	12	A25R	U25RT	U25RT	U25RT	-	-	-
2/0	13	A26R	U26RT	U26RT	U26RT	-	-	-
3/0	14	A27R	U27RT	U27RT	U27RT	-	-	-
4/0	15	A28R	U28RT	U28RT	U28RT	C28R	-	-
250	16	A29R	U29RT	U29RT	U29RT	C29R	-	-
300	17	A30R	U30RT	U30RT	U30RT	C30R	-	L30RT
350	18	A31R	U31RT	U31RT	U31RT	C31R	F31R	L31RT
400	19	A32R	U32RT	U32RT	U32RT	C32R	-	L32RT
500	20	A34R	U34RT	U34RT	U34RT	C34R	-	L34RT
600	22	-	U36RT	U36RT	U36RT	C36R	F36R	L36RT
750	24	-	-	U39RT	U39RT	C39R	F39R	L39RT
800	25	-	-	-	P40RT	C40R	-	-
1000	27	-	-	-	P44RT	C44R	F44R	L44RT
1500	31	-	-	-	P46RT	C46R	F46R	L46RT
2000	34	-	-	-	-	-	F48R	L48RT

* U Dies with a Y46 requires a P-UADP adaptor